

#### SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017 & ANSI/NCSL Z540-1-1994

### THERMAL PRODUCT SOLUTIONS, LLC 2821 Old Route 15

New Columbia, PA 17856

Anthony Bradley Phone: 570 538 7200

#### **CALIBRATION**

Valid To: October 31, 2021 Certificate Number: 3782.01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following calibrations  $^{1,7}$ :

#### I. Electrical – DC/Low Frequency

Parameter/Equipment	Range	CMC <sup>2, 6</sup> (±)	Comments
DC Voltage – Generate <sup>3</sup>	(0 to 110.0) mV (0.1 to 1.10) V (1.1 to 11.00) V	0.9 mV 0.02 V 0.09 V	Fluke 743B
DC Resistance – Generate <sup>3</sup>	(0 to 10) $\Omega$ (10 to 100) $\Omega$ (100 to 500) $\Omega$	0.02 Ω 0.09 Ω 0.62 Ω	Fluke 743B
DC Current – Generate <sup>3</sup>	(0 to 22) mA	0.12 mA	Fluke 743B
Electrical Calibration of RTD Indicating Systems <sup>3</sup> – 100 Ω, Pt 385	(-200 to 250) °C	0.8 °C	Fluke 743B
·			

hu

Parameter/Equipment	Range	CMC <sup>2</sup> (±)	Comments
Electrical Calibration of Thermocouple Indicating Systems <sup>3</sup> –			
Type J	(-100 to 800) °C	1.5 °C	Fluke 743B
Type K	(-100 to 1372) °C	1.7 °C	
Туре Т	(-200 to 0) °C (0 to 400) °C	0.79 °C 0.82 °C	

#### II. Thermodynamics<sup>4</sup>

Parameter/Equipment	Range	CMC <sup>2, 5</sup> (±)	Comments
Relative Humidity – Measure <sup>3</sup>	(10 to 95) % RH	3.5 % RH	Vaisala HMP77/M-170
Temperature – Measure <sup>3</sup>	(-80 to 0) °C (0 to 200) °C (0 to 710) °C	2.6 °C 1.4 °C 2.8 °C	Fluke 743B with calibrated thermocouple

<sup>&</sup>lt;sup>1</sup> This laboratory offers commercial calibration service and field calibration service.

hu

<sup>&</sup>lt;sup>2</sup> Calibration and Measurement Capability Uncertainty (CMC) is the smallest uncertainty of measurement that a laboratory can achieve within its scope of accreditation when performing more or less routine calibrations of nearly ideal measurement standards or nearly ideal measuring equipment. CMCs represent expanded uncertainties expressed at approximately the 95 % level of confidence, usually using a coverage factor of k = 2. The actual measurement uncertainty of a specific calibration performed by the laboratory may be greater than the CMC due to the behavior of the customer's device and to influences from the circumstances of the specific calibration.

<sup>&</sup>lt;sup>3</sup> Field calibration service is available for this calibration and this laboratory meets A2LA *R104 – General Requirements: Accreditation of Field Testing and Field Calibration Laboratories* for these calibrations. Please note the actual measurement uncertainties achievable on a customer's site can normally be expected to be larger than the CMC found on the A2LA Scope. Allowance must be made for aspects such as the environment at the place of calibration and for other possible adverse effects such as those caused by transportation of the calibration equipment. The usual allowance for the actual uncertainty introduced by the item being calibrated, (e.g. resolution) must also be considered and this, on its own, could result in the actual measurement uncertainty achievable on a customer's site being larger than the CMC.

- <sup>4</sup> Includes Measure Equipment performed by comparison, actual uncertainty may be larger due to resolution of unit under test.
- <sup>5</sup> The type of instrument or material being calibrated is defined by the parameter. This indicates the laboratory is capable of calibrating instruments that measure or generate the values in the ranges indicated for the listed measurement parameter.
- <sup>6</sup> The stated measured values are determined using the indicated instrument (see Comments). This capability is suitable for the calibration of the devices intended to measure or generate the measured value in the ranges indicated. CMCs are expressed as either a specific value that covers the full range or as a percent or fraction of the reading plus a fixed floor specification.
- <sup>7</sup> This scope meets A2LA's *P112 Flexible Scope Policy*.

hu



# Accredited Laboratory

A2LA has accredited

## THERMAL PRODUCT SOLUTIONS, LLC

New Columbia, PA

for technical competence in the field of

### Calibration

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 *General requirements for the competence of testing and calibration laboratories.* This laboratory also meets the requirements of ANSI/NCSL Z540-1-1994 and *R205 – Specific Requirements: Calibration Laboratory Accreditation Program.* This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 April 2017).



Presented this 20th day of March 2020.

Vice President, Accreditation Services

For the Accreditation Council

Certificate Number 3782.01

Valid to October 31, 2021